

WANLONG CABLE

PROFESSIONAL CABLE MANUFACTURER

RG58U 95%

Hangzhou Lin'an Wanlong Cable Co., Ltd

317 Jintian Road, Lin'an, Hangzhou, China 311300

Mob:+86-13968032911 Tel:+86-571-61078177

Fax:+86-571-61078123

Website: www.wanlongcable.cn

E-mail: wanlongcable@hotmail.com wanlongcable2@outlook.com

PRODUCT DESCRIPTION:

BARE COPPER, SPE, BONDED LAMINATED ALUMINUM OR COPPER FOIL,
95% TINNED COPPER BRAID OR COPPER CLAD ALUMINUM, PVC

CENTER CONDUCTOR: 0.84 mm BARE COPPER

DIELECTRIC:

SOLID POLYETHYLENE

NOMINAL DIAMETER OVER DIELECTRIC: 2.95 mm

SHIELD:

1ST SHIELD: LAMINATED ALUMINUM TAPE BONDED
TO THE DIELECTRIC

2nd SHIELD: 112*0.12 mm TINNED COPPER BRAID
OR COPPER CLAD ALUMINUM BRAID
95% COVERAGE

JACKET:

PVC

NOMINAL DIAMETER OVER JACKET: 4.90 mm

NOMINAL JACKET THICKNESS: 0.73 mm

ELECTRICAL PROPERTIES:

IMPEDANCE: 50.0 +/- 2.0 Ohms

VELOCITY OF PROPAGATION: 66.0% NOMINAL



WANLONG CABLE

WANLONG CABLE

PROFESSIONAL CABLE MANUFACTURER

RG58U 95%

Hangzhou Lin'an Wanlong Cable Co., Ltd

317 Jintian Road, Lin'an, Hangzhou, China 311300

Mob:+86-13968032911 Tel:+86-571-61078177

Fax:+86-571-61078123

Website: www.wanlongcable.cn

E-mail: wanlongcable@hotmail.com wanlongcable2@outlook.com

ATTENUATION @ 68°F (20°C):

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.8 dB	2.7 dB
10 MHz	1.1 dB	3.6 dB
50 MHz	2.5 dB	8.2 dB
100 MHz	3.8 dB	12.5 dB
200 MHz	5.6 dB	18.4 dB
400 MHz	8.4 dB	27.5 dB
700 MHz	11.7 dB	38.4 dB
900 MHz	13.7 dB	44.9 dB
1000 MHz	14.5 dB	47.5 dB

WANLONG CABLE